



Winsig CSM700 Broadband Antenna

The WINSIG CSM700 is a compact low-profile omnidirectional LTE antenna that provides excellent coverage for mobile and fixed data applications from 698 MHz to 2.7 GHz.

This antenna is design to enhance Wi-Fi and Broadband mobile reception

The antenna features an attractive, compact housing which can be used in both indoor and outdoor applications. The CSM700 is fitted with a 14 mm stud mount incorporating an integrated rubber O-ring seal.

This antenna may also be purchased as an integrated solution with the Winsig 3.0 Ultra terrestrial TV antenna for a complete entertainment solution.



Technical Specifications

- ASA radome is available in white or Black, and is UV stable and ideal for outdoor use
- Low profile design for maximum overhead clearance on the van (80mm above mounting surface)
- Stud mounting offers ease of installation in the field
- Optional Stainless Steel mount is also available for adaption to vertical surfaces or bull bars
- Standard configuration includes 5m RG58 cable SMA connector
- Weight: 600g (excluding std. co-axial cable)

Model Number	CSM 700		
Nominal Gain dB	2.0	3.5	5.0
Frequency MHz	696-960	1710-2170	2300-2700
Tuned Bandwidth MHz	Full		
VSWR	2.0:1		
Nominal Impedance Ω	50		
Power W	10		

